

DOUBLE CAPACITY SINGLE UNIT



Delta Therm Hot Oil Systems



Double capacity for heating and cooling. Name brand components, features you won't find anywhere else, at a price you will find surprisingly competitive. The Delta Therm Hot Oil Unit gives you more.

MORE HEATING CAPACITY

A 12 KW flanged heater is standard on the Delta Therm Hot Oil Unit. That's twice the size of 6 KW heaters available on traditional units. Double capacity. At precise temperatures.

MORE COOLING CAPACITY

The 3.7 square foot shell and tube heat exchanger provides twice the cooling ability of the standard 1.5 square foot exchanger found on competitive models.

MORE PRECISE CONTROL

Commercially available, "off-the-shelf" controller (with dual display), features micro-processor, PID control of a mercury heating contactor, provides faster response during heating cycles. This means higher productivity.

MORE FEATURES

The state of the art design assures precise temperature tolerances. A positive displacement pump delivers 10 GPM @30 PSI. Easy-to-read pilot lights indicate separate functions of the unit—Power On, Heater On, Cooling On. Fused protection on all power components. Sub-surface mounting of controls reduces possible damage to instruments in an industrial environment.

MORE VALUE

Special features and exceptional quality doesn't mean an inflated cost. The Delta Therm Hot Oil Unit is priced to be competitive, so you get more performance for your money.

More consistency. More quality. And, in the long run, more value.

A complete list of specifications and diagrams appear on the back page.