

	Model	Unit Dimensions*	Temperature Range (F)	Heater Capacity	Pump Capacity	Motor HP	Min. Heat Exchanger Size
6 KW	T-1111M	16" X 30" X 46"	50-550	6KW	10 GPM@30 PSI	3/4	1.5
	T-1112M	16" X 30" X 46"	50-550	6KW	18 GPM@30 PSI	1	1.5
	T-1113M	16" X 30" X 46"	50-550	6KW	18 GPM@50 PSI	1-1/2	1.5
	T-1214M	16" X 30" X 46"	50-550	6KW	24 GPM@50 PSI	2	1.5
12 KW	T-1221M	16" X 30" X 46"	50-550	12KW	10 GPM@30 PSI	3/4	1.5
	T-1222M	16" X 30" X 46"	50-550	12KW	18 GPM@30 PSI	1	1.5
	T-1223M	16" X 30" X 46"	50-550	12KW	18 GPM@50 PSI	1-1/2	1.5
	T-1224M	16" X 30" X 46"	50-550	12KW	24 GPM@50 PSI	2	1.5
18 KW	T-1232M	16" X 30" X 46"	50-550	18KW	18 GPM@30 PSI	1	1.5
	T-1233M	16" X 30" X 46"	50-550	18KW	18 GPM@50 PSI	1-1/2	1.5
	T-1234M	16" X 30" X 46"	50-550	18KW	24 GPM@50 PSI	2	1.5
	T-1435M	42" X 38" X 55"	50-550	18KW	50 GPM@50 PSI	3	1.5
24 KW	T-1242M	16" X 30" X 46"	50-550	24KW	18 GPM@30 PSI	1	1.5
	T-1243M	16" X 30" X 46"	50-550	24KW	18 GPM@50 PSI	1-1/2	1.5
	T-1244M	16" X 30" X 46"	50-550	24KW	24 GPM@50 PSI	2	1.5
	T-1445M	42" X 38" X 55"	50-550	24KW	50 GPM@50 PSI	3	1.5
36 KW	T-1254M	16" X 30" X 46"	50-550	36KW	24 GPM@50 PSI	2	4.0
	T-1455M	42" X 38" X 55"	50-550	36KW	50 GPM@50 PSI	3	4.0
	T-1956M	42" X 38" X 55"	50-550	36KW	90 GPM@50 PSI	5	4.0
48 KW	T-1465M	42" X 38" X 55"	50-550	48KW	50 GPM@50 PSI	3	11.1
	T-1966M	42" X 38" X 55"	50-550	48KW	90 GPM@50 PSI	5	27.0

* Unit Dimensions might vary depending on the heat exchanger size