

## 550° OIL UNITS

	MODEL	UNIT DIMENSIONS	TEMP RANGE (F)	HEATER CAPACITY	PUMP CAPACITY	HP	COOLING CAPACITY <sup>1</sup>
6 KW	T-1011M	16" X 30" X 46"	50-550	6KW	10 GPM@30 PSI	3/4	SEE TABLE
	T-1012M	16" X 30" X 46"	50-550	6KW	18 GPM@30 PSI	1	SEE TABLE
	T-1013M	16" X 30" X 46"	50-550	6KW	18 GPM@50 PSI	1-1/2	SEE TABLE
	T-1014M	16" X 30" X 46"	50-550	6KW	24 GPM@50 PSI	2	SEE TABLE
12 KW	T-1021M	16" X 30" X 46"	50-550	12KW	10 GPM@30 PSI	3/4	SEE TABLE
	T-1022M	16" X 30" X 46"	50-550	12KW	18 GPM@30 PSI	1	SEE TABLE
	T-1023M	16" X 30" X 46"	50-550	12KW	18 GPM@50 PSI	1-1/2	SEE TABLE
	T-1024M	16" X 30" X 46"	50-550	12KW	24 GPM@50 PSI	2	SEE TABLE
18 KW	T-1032M	16" X 30" X 46"	50-550	18KW	18 GPM@30 PSI	1	SEE TABLE
	T-1033M	16" X 30" X 46"	50-550	18KW	18 GPM@50 PSI	1-1/2	SEE TABLE
	T-1034M	16" X 30" X 46"	50-550	18KW	24 GPM@50 PSI	2	SEE TABLE
	T-1035M	42" X 38" X 55"	50-550	18KW	50 GPM@50 PSI	3	SEE TABLE
24 KW	T-1042M	16" X 30" X 46"	50-550	24KW	18 GPM@30 PSI	1	SEE TABLE
	T-1043M	16" X 30" X 46"	50-550	24KW	18 GPM@50 PSI	1-1/2	SEE TABLE
	T-1044M	16" X 30" X 46"	50-550	24KW	24 GPM@50 PSI	2	SEE TABLE
	T-1045M	42" X 38" X 55"	50-550	24KW	50 GPM@50 PSI	3	SEE TABLE
36 KW	T-1054M	16" X 30" X 46"	50-550	36KW	24 GPM@50 PSI	2	SEE TABLE
	T-1055M	42" X 38" X 55"	50-550	36KW	50 GPM@50 PSI	3	SEE TABLE
	T-1056M	42" X 38" X 55"	50-550	36KW	90 GPM@50 PSI	5	SEE TABLE
48 KW	T-1065M	42" X 38" X 55"	50-550	48KW	50 GPM@50 PSI	3	SEE TABLE
	T-1066M	42" X 38" X 55"	50-550	48KW	90 GPM@50 PSI	5	SEE TABLE

COOLING TABLE <sup>1</sup>	
UNIT CODE	COOLING CAPACITY
0	HEAT ONLY
1	58,000 BTU/HR (1.7 KW)
2	147,000 BTU/HR (43 KW)
3	256,000 BTU/HR (75 KW)
4	402,000 BTU/HR (118 KW)
5	458,000 BTU/HR (133 KW)

<sup>1</sup> COOLING IS CALCULATED USING STANDARD FLOW CONDITIONS WITH 65 °F COOLING AND A PROCESS TEMPERATURE OF 550 °F